

**RIMSO** since 1964  
**BATTERY**



# Long Life High Performance Battery


for Automotive application

**Head Office:**


21/1, Court House Street, Dhaka-1100  
Tel : +88-02-9567825, +8801756482597, Fax : +88 02 9567826

**Factory:**

Barpa, Masabo, Rupgonj, Narayangonj  
Bangladesh, Mobile : +88 01720534479  
E-mail: info@rimsobd.com, rimsogroups@yahoo.com

 Rimso Battery

 Rimso Battery

 Rimso Battery

Hotline : 01618-8RIMSO  
01733-387000  
01733-387100

[www.rimsobd.com](http://www.rimsobd.com)

# PRODUCT SPECIFICATION

Sl.	Battery Type	Nominal Voltage (V)	Plate /Cell (Pcs.)	Capacity (AH) @ 20 HR.	Container Type (PP)	Dimension (approx.)			Dry Weight (kg)	Acid Volume (Litre)
						L (mm)	W (mm)	H (mm)		
<b>AUTOMOTIVE</b>										
1	NS 40	12	9	32	NS40	194	128	223	7.5	2.7
2	NS 40Z	12	11	35	NS40				8.9	2.6
3	NS 40ZL	12	11	35	NS40L				8.9	2.6
4	NS60	12	13	45	NS60	237	129	225	10.4	3.0
5	NS 60L	12	13	45	NS60L				10.4	3.0
6	NS 60 S	12	13	45	NS60S				10.4	3.0
7	N50	12	9	50	N50	257	173	215	13.2	4.0
8	N50Z	12	11	60	N50				14.1	3.9
9	N50 ZL	12	11	60	N50L				14.1	3.9
10	NS 70	12	13	65	N50				14.9	3.9
11	N 70	12	13	70	N70	300	169	217	15.4	5.7
12	N 70Z	12	15	75	N70				16.5	5.7
13	N 70ZL	12	15	75	N70L				16.5	5.7
14	NX120-7	12	17	80	N70				18.7	5.0
15	NX120-7L	12	17	80	N70L				18.7	5.0
16	DIN 55	12	11	55	DIN55	242	175	190	12.7	4.5
17	DIN 88	12	17	88	DIN88	370	175	190	16.7	5.8
18	N100	12	17	100	N100	412	177	229	19.2	7.8
19	N100 Z	12	19	105	N100				21	7.6
20	NS 120	12	21	110	N100				22	7.4
21	N 120	12	21	120	N120	498	185	230	24.9	9.1
22	N150	12	25	150	N150	503	220	223	33.2	10.8
23	N200	12	29	200	N200	510	271	235	35.3	16.6
24	RBC 15	12	15	-	N70	300	169	217	17.3	5.5
25	RBC 17	12	17	-	N100	412	177	229	19.9	7.8
26	RBC 21	12	21	-	N120	498	185	230	24.8	9.1
27	RBC 27	12	27	-	N150	503	220	223	31.4	10.7
28	RBC 29	12	29	-	N200	510	271	235	32.6	16.6

